Printing date 02/14/2014

Reviewed on 01/03/2014

Product identij	fier			
Trade name: <u>T</u>	Toluene, Technical Gra	<u>ude</u>		
Article number	r: T7616			
CAS Number:				
108-88-3				
EC number: 203-625-9				
Index number:				
601-021-00-3				SOLUTIONS
Details of the s	supplier of the safety do	ata sheet		
Manufacturer/				
Aqua Solutions				
6913 Highway DEER PARK, 7				
USA	IX //330			
800-256-2586				
Information de				
Product safety				
Technical Coor	rdinator m sherman@aquasoluti	ions ora		
	ephone number:	ions.org		
Chemtrec: 800				
Canutec: 613-9	996-6666			
Hazard(s) id	lentification			
	of the substance or mix	xture		
Classification	, v	xture		
Classification of Classificatio of Classification of Classification of Classificatio	of the substance or mix			
Classification of GHS Flam. Liq. 2 H	of the substance or mix			
Classification of GHS GHS Flam. Liq. 2 H	of the substance or mix 502 Flame 1225 Highly flammable 508 Health hazard		born child.	
Classification of GHS Flam. Liq. 2 H GHS Repr. 2 H	of the substance or mix 502 Flame 1225 Highly flammable 508 Health hazard 1361 Suspected of dam	e liquid and vapor.		
Classification of GHS Flam. Liq. 2 H Construction of GHS Repr. 2 H STOT RE 2 H	of the substance or mix 502 Flame 1225 Highly flammable 508 Health hazard 1361 Suspected of dama 1373 May cause damag	e liquid and vapor. aging fertility or the un	olonged or repeated e	
Classification of GHS Flam. Liq. 2 H GHS Repr. 2 H STOT RE 2 H	of the substance or mix 502 Flame 1225 Highly flammable 508 Health hazard 1361 Suspected of dama 1373 May cause damag 1304 May be fatal if sw	e liquid and vapor. aging fertility or the un ge to organs through pr	olonged or repeated e	
Classification of GHS Flam. Liq. 2 H Flam. Liq. 2 H GHS Repr. 2 H STOT RE 2 H Asp. Tox. 1 H GHS	of the substance or mix 502 Flame 1225 Highly flammable 508 Health hazard 1361 Suspected of dama 1373 May cause damag 1304 May be fatal if sw	e liquid and vapor. aging fertility or the un ge to organs through pr vallowed and enters airy	olonged or repeated e	
Classification GHS Flam. Liq. 2 H Flam. Liq. 2 H GHS Repr. 2 H STOT RE 2 H Asp. Tox. 1 H Composition GHS Skin Irrit. 2 H	of the substance or mix 502 Flame 1225 Highly flammable 508 Health hazard 1361 Suspected of dama 1373 May cause damag 1304 May be fatal if sw	e liquid and vapor. aging fertility or the un ge to organs through pr vallowed and enters airv	olonged or repeated e	

Printing date 02/14/2014

Reviewed on 01/03/2014

Trade name: Toluene, Technical Grade



• Index number: 601-021-00-3

(Contd. on page 3)

Printing date 02/14/2014

Reviewed on 01/03/2014

Trade name: Toluene, Technical Grade

(Contd. of page 2)

4 First-aid measures

- · Description of first aid measures
- · General information:
- Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.
- After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: If symptoms persist consult doctor.
- Information for doctor:
- Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed
- No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:
- CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- For safety reasons unsuitable extinguishing agents: Water with full jet
- Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: No special measures required.

6 Accidental release measures

- \cdot Personal precautions, protective equipment and emergency procedures
- Wear protective equipment. Keep unprotected persons away.
- Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- Methods and material for containment and cleaning up:
- Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

- Ensure adequate ventilation.
- · Reference to other sections
- See Section 7 for information on safe handling.
- See Section 8 for information on personal protection equipment.
- See Section 13 for disposal information.

7 Handling and storage

- · Handling:
- Precautions for safe handling No special precautions are necessary if used correctly.
- Information about protection against explosions and fires: Keep ignition sources away - Do not smoke.
- Protect against electrostatic charges.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.

(Contd. on page 4)

USA

Printing date 02/14/2014

Reviewed on 01/03/2014

Trade name: Toluene, Technical Grade

(Contd. of page 3)

Further information about storage conditions: Keep receptacle tightly sealed.
Store in cool, dry conditions in well sealed receptacles.
Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

• Additional information about design of technical systems: No further data; see item 7.

· Control parameters

• Components with limit values that require monitoring at the workplace: 108-88-3 Toluene	
108-88-3 Toluene	
PEL Long-term value: 200 ppm Ceiling limit value: 300; 500* ppm *10-min peak per 8-hr shift	
REL Short-term value: 560 mg/m ³ , 150 ppm Long-term value: 375 mg/m ³ , 100 ppm	
TLV Long-term value: 75 mg/m ³ , 20 ppm BEI	
· Ingredients with biological limit values:	
108-88-3 Toluene	
BEI 0.02 mg/L Medium: blood Time: prior to last shift of workweek Parameter: Toluene	
0.03 mg/L Medium: urine Time: end of shift Parameter: Toluene	
0.3 mg/g creatinine Medium: urine Time: end of shift Parameter: o-Cresol with hydrolysis (background)	
• Additional information: The lists that were valid during the creation were used as basis.	
 Exposure controls Personal protective equipment: General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work. Avoid contact with the skin. Avoid contact with the eyes and skin. Breathing equipment: In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure respiratory protective device that is independent of circulating air. (Contd. on page 1997) 	

Printing date 02/14/2014

Reviewed on 01/03/2014

(Contd. of page 4)

Trade name: Toluene, Technical Grade

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the

chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation \cdot *Material of gloves*

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

 \cdot Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

• Eye protection:



Tightly sealed goggles

Information on basic physical and c	hemical properties
General Information	
Appearance:	Y • • • 1
Form: Color:	Liquid Colorless
Odor:	Aromatic
Odour threshold:	Not determined.
pH-value:	Not determined.
Change in condition	
Melting point/Melting range:	-95 °C (-139 °F)
Boiling point/Boiling range:	110-111 °C (230-232 °F)
Flash point:	4 °C (39 °F)
Flammability (solid, gaseous):	Not applicable.
Ignition temperature:	535 °C (995 °F)
Decomposition temperature:	Not determined.
Auto igniting:	Not determined.
Danger of explosion:	Product is not explosive. However, formation of explosive air/vapo mixtures are possible.
Explosion limits:	
Lower:	1.2 Vol %
Upper:	7 Vol %
Vapor pressure at 20 °C (68 °F):	29 hPa (22 mm Hg)
Density at 20 °C (68 °F):	0.87 g/cm ³ (7.26 lbs/gal)

Printing date 02/14/2014

Reviewed on 01/03/2014

Trade name: Toluene, Technical Grade

		(Contd. of page
· Relative density	Not determined.	
· Vapour density	Not determined.	
· Evaporation rate	Not determined.	
· Solubility in / Miscibility with		
Water at 15 °C (59 ° F):	0.5 g/l	
· Partition coefficient (n-octanol/wa	t ter): Not determined.	
· Viscosity:		
Dynamic at 20 °C (68 °F):	0.6 mPas	
Kinematic:	Not determined.	
• Other information	No further relevant information available.	

10 Stability and reactivity

- · Reactivity
- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

· Information on toxicological effects

• Acute toxicity:

· LD/LC50 values that are relevant for classification:

OralLD505000 mg/kg (rat)DermalLD5012124 mg/kg (rabbit)

Inhalative LC50/4 h 5320 mg/l (mouse)

· Primary irritant effect:

- on the skin: Irritant to skin and mucous membranes.
- on the eye: No irritating effect.
- Sensitization: No sensitizing effects known.
- · Additional toxicological information:
- · Carcinogenic categories

· IARC (International Agency for Research on Cancer)

108-88-3 Toluene

· NTP (National Toxicology Program) Substance is not listed.

12 Ecological information

· Toxicity

• Aquatic toxicity: No further relevant information available.

- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.

(Contd. on page 7)

USA

3

Printing date 02/14/2014

Reviewed on 01/03/2014

Trade name: Toluene, Technical Grade

(Contd. of page 6)

- · Mobility in soil No further relevant information available.
- $\cdot \textit{Additional ecological information:}$
- · General notes:
- Water hazard class 2 (Assessment by list): hazardous for water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground.
- · Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:
- Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

UN-Number		
DOT, IMDG, IATA	UN1294	
UN proper shipping name		
DOT	Toluene	
IMDG, IATA	TOLUENE	
Transport hazard class(es)		
DOT		
PLAMABLE LOUD		
Class	3 Flammable liquids.	
Label	3	
IMDG, IATA		
Class	3 Flammable liquids.	
Label	3	
Packing group		
DOT, IMDG, IATA	II	
Environmental hazards:		
Marine pollutant:	No	
Special precautions for user	Warning: Flammable liquids	

Printing date 02/14/2014

Reviewed on 01/03/2014

Trade name: Toluene, Technical Grade

		(Contd. of page 7)
· Danger code (Kemler):	33	
• EMS Number:	F- E , S - D	
• Transport in bulk according to Annex	II of	
MARPOL73/78 and the IBC Code	Not applicable.	
· UN ''Model Regulation'':	UN1294, Toluene, 3, II	

15 Regulatory information

 \cdot Safety, health and environmental regulations/legislation specific for the substance or mixture \cdot Sara

- Section 355 (extremely hazardous substances): Substance is not listed.
- Section 313 (Specific toxic chemical listings): Substance is listed.
- TSCA (Toxic Substances Control Act): Substance is listed.

· Proposition 65

- · Chemicals known to cause cancer: Substance is not listed.
- Chemicals known to cause reproductive toxicity for females: Substance is listed.
- · Chemicals known to cause reproductive toxicity for males: Substance is not listed.
- Chemicals known to cause developmental toxicity: Substance is listed.

· Carcinogenic categories

· EPA (Environmental Protection Agency)

108-88-3 Toluene

· TLV (Threshold Limit Value established by ACGIH)

108-88-3 Toluene

· NIOSH-Ca (National Institute for Occupational Safety and Health) Substance is not listed.

- · OSHA-Ca (Occupational Safety & Health Administration) Substance is not listed.
- *GHS label elements* The substance is classified and labeled according to the Globally Harmonized System (GHS). *Hazard pictograms*



· Signal word Danger

· Hazard statements

Highly flammable liquid and vapor.

Causes skin irritation.

Suspected of damaging fertility or the unborn child.

May cause drowsiness or dizziness.

May cause damage to organs through prolonged or repeated exposure.

May be fatal if swallowed and enters airways.

· Precautionary statements

Keep away from heat/sparks/open flames/hot surfaces. No smoking. Use explosion-proof electrical/ventilating/lighting/equipment. IF SWALLOWED: Immediately call a POISON CENTER/ doctor/... If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. Store locked up. Dispose of contents/container in accordance with local/regional/national/international regulations.

. (Contd. on page 9)

USA

II

A4

Printing date 02/14/2014

Reviewed on 01/03/2014

Trade name: Toluene, Technical Grade

(Contd. of page 8)

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Department issuing MSDS: Environment protection department.

· Abbreviations and acronvms: ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation IATA: International Air Transport Association ACGIH: American Conference of Governmental Industrial Hygienists EINECS: European Inventory of Existing Commercial Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent Flam. Liq. 2: Flammable liquids, Hazard Category 2 Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2 Repr. 2: Reproductive toxicity, Hazard Category 2 STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3 STOT RE 2: Specific target organ toxicity - Repeated exposure, Hazard Category 2 Asp. Tox. 1: Aspiration hazard, Hazard Category 1

[·] Contact: Mr. Nelson