



IntelliCAL™ ISENH4181 Ammonium Ion Selective Electrode (ISE), 1 meter cable

Product #: ISENH418101

IntelliCAL™ ISENH4181 is a digital, combination ammonium ion selective electrode (ISE) with a non-refillable, double junction reference and built-in temperature sensor. The IntelliCAL ISENH4181 probe is available with a 1 or 3 meter cable and is intended for laboratory use. The ISENH4181 is ideal for measuring ammonium concentrations in wastewater, drinking water and general water quality applications. The ISENH4181's solid-state sensor design eliminates membrane replacement and allows for dry storage of the ISE.

Utilizes a unique solid-state sensor technology that eliminates costly membrane replacements.

Traditional PVC-membrane ISEs require membrane replacement every 2-3 months. The IntelliCAL ISENH4181 Ammonium ISE's unique solid-state sensor technology eliminates the need for frequent membrane replacement by using a solid gel ion exchange behind the ion-selective membrane versus the liquid ion exchange used in most ISEs. This design allows users to get up to 2 years of life from their ISE without membrane replacement – saving the time and costly expense of frequently exchanging membranes.

Requires virtually no maintenance

The solid-state sensor design allows for DRY storage of the ISE without a shelf life. Also, the probe does not require the electrolyte to be refilled.

Fast, stable, and accurate results

IntelliCAL digital probes lock on the result when the measurement is stable, removing the guesswork in having a moving number. Additionally, the probe's large annular reference junction provides maximum surface area between sample and reference electrolyte for fast measurement stability. And the solid-state sensor design doesn't allow the membrane to flex or undergo surface area changes, leading to more stability in results over a variety of samples.

Ultimate traceability in measurement history

Stored time and date stamp for each measurement, operator and sample ID, calibration history, parameter, and probe serial number

Can be moved between meters without the need to re-calibrate or re-enter measurement settings

Ideal for a multi-user environment with multiple HQD series Laboratory and Portable meters

Specifications

Accuracy:	±0.02mV or 0.05%, whichever is greater
Cable Length:	1 m
Connector:	HQD specific
Diameter:	12 mm
Dimensions (D x L):	12 mm x 220 mm
Filling Solution:	Non-refillable driTEK gel
ISA Required:	2980699
Junction:	Porous PTFE Annular Ring
Length:	220 mm
Material:	Sensor Body: Epoxy
Parameter:	Ammonium
Probe Type:	Standard

Reference Type:	Ag/AgCl
Resolution:	2, 3, 4 significant digits selectable
Sensor Type:	Solid-state PVC membrane
Special Feature:	Dry storage & fast response time. No replacement membranes.
Temperature Range:	0 to 50 °C

What's in the box?

Includes: IntelliCAL ISENH4181 combination Ammonium ISE with integrated temperature sensor, calibration certificate, and Basic User Manual.

Required Accessories

- Ammonium Ionic Strength Adjustor (ISA) Powder Pillows, pk/100 (Item 2980699)